

# EdmDrill™ FT300

Fully Enclosed CNC EDM Drilling Machine




The EdmDrill™ FT300 is designed for high-production work in industries such as Aerospace, Automotive, Medical and Cutting Tools. It is fully operable and serviceable from the front and rear of the machine. EDM Milling feature greatly expands the FT300's capabilities by enabling the machining of 3 dimensional shapes such as gates and diffusers (ESPRIT® CAM recommended to simplify programming).

- 5 Axis EDM drilling machine with electrode changer
- Machines can be placed side-by-side to save floor space
- 25 lbs. weight capacity at tilt-rotary table
- Reliable drilling depth control
- EDM Milling capability
- Accepts robotic part loading/unloading
- Ergonomic design

# EdmDrill™ FT300 Fully Enclosed CNC EDM Drilling Machine



**SINUMERIK ONE CNC, TOP22 Blackline**  
Plus multitouch panel and SINAMICS drives with absolute motors.



## NIKKEN 5AX-SW105

A-Axis Travel	±90°
B-Axis Travel	±180°
Fixture and Part Weight	25 lb. (11.3kg)



## AEC24 AUTOMATIC ELECTRODE CHANGER

Number of Drill Chucks	24
Electrode Diameter Range	0.012 in. - 0.118 in. (0.3mm - 3.0mm)
Collets/Sizes	12 each 0.020 in. (0.5mm) 12 each 0.040 in. (1.0mm)
Maximum Electrode Length	16 in. (400mm)
Compressed Air Required	70 - 90 PSI / Dry / 2.5 CFM
Emergency Drill Chuck	0.010 in. - 0.118 in (0.25mm - 3.0mm) range

## STANDARD FEATURES

X-Axis Travel:	12"
Y-Axis Travel:	6"
Z-Axis Travel:	16"
W-Axis Travel:	14"
Electrode Diameter Range:	.1-6.5mm
Maximum Table Weight Capacity:	25 lbs.
Machine Weight:	1500 lbs.
Machine Footprint:	40"X60"

## CONTROL

Controller	Siemens SINUMERIK ONE
Display Type	22 in. (558 mm) High-resolution LCD
Displayed Axes	X, Y, W, Z, A, B
Controlled Axes	X, Y, W, Z, A, B
Motors (X, Y, W)	AC Servo
Feedback (X, Y)	Rotary Encoder
Feedback (W)	Rotary Encoder
Feedback (Z)	Rotary Encoder
Program Storage	10MB (Expandable to 4GB)
Drilling Modes	Manual and Automatic
Spindle Rotation	Bi-Directional
USB Port	Standard
Servo Feed Rate	Programmable

## MOTORS AND DRIVERS

Motors (X, Y, W)	Siemens AC Servo
Feedback (X, Y, W)	Encoder
Z Motor	DC with Siemens Encoder
Positioning	±0.0005 in.
Repeatability	0.0002 in.

## POWER SUPPLY

Type	Variable Frequency DC
Switching	High Current FET
Output Amperage	30/57 (mean/peak)
Amperage Range (Ip)	1 to 57 Amps (3 Amp increments)
On-Time Setting (TON)	1-100mSec (1mSec increments)
Off-Time Setting (TOFF)	1-100mSec (1mSec increments)
Meters	Voltmeter and Ammeter
Capacitance Range	0 to 1.15mFarad (0.05 increments)

©2025 CURRENT EDM. 1009.0425

## INTERNATIONAL HEADQUARTERS

2577 Leghorn Street  
Mountain View, CA 94043  
(650) 966-9676 phone  
(650) 966-1881 fax

## SALES OFFICE & SHOWROOM

9201 Penn Avenue South, Suite 40  
Bloomington, MN 55431 USA  
(763) 476-2290 phone  
(763) 476-2190 fax

## DISTRIBUTED BY:

[WWW.CURRENTEDM.COM](http://WWW.CURRENTEDM.COM) • email: [INFO@CURRENTEDM.COM](mailto:INFO@CURRENTEDM.COM)

Precision EDM Drilling Machines

**Current EDM**